Weak Bisimilarity and Regularity of BPA is *EXPTIME*-hard*

Richard Mayr
Department of Computer Science
Albert-Ludwigs-University Freiburg
Georges-Koehler-Allee 51, D-79110 Freiburg, Germany.
E-mail: mayrri@informatik.uni-freiburg.de

Abstract

We show that checking weak bisimulation equivalence of two context-free processes (also called BPA-processes) is *EXPTIME*-hard, even under the condition that the processes are normed. Furthermore, checking weak regularity (finiteness up to weak bisimilarity) for context-free processes is *EXPTIME*-hard as well.

Keywords: Context-free processes, BPA, weak bisimulation, complexity

1 Introduction

Bisimulation equivalence plays a central role in the theory of process algebras [13]. The decidability and complexity of bisimulation problems for infinite-state systems has been studied intensively (see [4, 16] for surveys). Here we consider the complexity of checking weak and strong bisimulation equivalence for several subclasses of pushdown automata (PDA). BPA (Basic Process Algebra; also called context-free processes) are equivalent to the subclass of pushdown automata where the finite control has size 1. The subclasses of *normed* PDA and BPA (denoted as nPDA and nBPA) satisfy the additional condition that from every reachable configuration it is possible to empty the

*Technical report number 181, Department of Computer Science, Albert-Ludwigs-University Freiburg, December 2002, http://www.informatik.uni-freiburg.de/tr/complete.html

stack. A normed PDA/BPA is called *totally normed* if the stack can always be emptied, but not by internal τ-actions alone.

The state of the art: Strong bisimilarity was shown to be decidable for normed PDA by Stirling [20], and later for general PDA by Sénizergues [14]. However, no upper complexity bound for this problem is known so far. The best known lower bound is *EXPTIME*-hardness [10], which holds even for (totally) normed PDA. Weak bisimulation equivalence for (normed) PDA is undecidable [19].

The best known algorithm for strong bisimilarity of BPA requires doubly exponential time (and space) [5], while the best known lower bound is *PSPACE*-hardness [18]. However, strong bisimilarity of normed BPA is decidable in polynomial time [8]. The decidability of weak bisimilarity for BPA is an open question. The undecidability proof for PDA does not carry over to BPA, and it is widely conjectured that this problem is decidable for BPA. It is known that weak bisimilarity is decidable for the subclass of totally normed BPA [7]. The best known lower bound for weak bisimilarity of general BPA was *PSPACE*-hardness [22], while the best lower bound for weak bisimilarity of (totally) normed BPA was only $\mathcal{NP}$-hardness [22].

Our contribution. We show that weak bisimilarity of BPA is *EXPTIME*-hard, even for normed BPA. Then we use this result to show that the problem of deciding if a given BPA is weakly regular (finite up to weak bisimilarity) is also *EXPTIME*-hard. This improves a previously known DP lower bound [15].

2 Definitions

BPA processes correspond to pushdown automata with a finite-control of size 1. They can also be described by $(1, S)$-PRS in the framework of process rewrite systems (PRS) [12]. Let $Act = \{a, b, c, \ldots\}$ and $Const = \{\epsilon, X, Y, Z, \ldots\}$ be disjoint countably infinite sets of *actions* and *process constants*, respectively. The class of *sequential process expressions* S is defined by $E ::= \epsilon \mid X \mid E.E$, where $X \in Const$ and ϵ is a special constant that denotes the empty expression. Intuitively, '.' is a sequential composition. We do not distinguish between expressions related by *structural congruence* which is given by the following laws: '.' is associative and 'ϵ' is a unit for '.'. A BPA is a finite set Δ of *rules* which have the form $E \stackrel{a}{\rightarrow} F$, where $E, F \in S$, $E \neq \epsilon$ and $a \in Act$. $Const(\Delta)$ and $Act(\Delta)$ denote the sets of process constants and actions which are used in the rules of Δ, respectively (note that these sets are finite).

Each BPA Δ defines a unique labeled transition system where states are process expressions. $Act(\Delta)$ is the set of labels. The transitions are determined by Δ and the following inference rules: $\dfrac{(E \stackrel{a}{\to} F) \in \Delta}{E \stackrel{a}{\to} F}$ $\qquad$ $\dfrac{E \stackrel{a}{\to} E'}{E.F \stackrel{a}{\to} E'.F}$

We extend the notation $E \stackrel{a}{\to} F$ to elements of Act^* in a standard way. Moreover, we say that F is *reachable* from E if $E \stackrel{w}{\to} F$ for some $w \in Act^*$. A BPA-process (α, Δ) is given by an expression $\alpha \in S$ and a set of rules Δ. Δ is omitted if it is clear from the context. The length of a string of symbols α is denoted by $|\alpha|$.

Definition 2.1 A process is **normed** if from every reachable configuration there is a terminating computation. We say that a pushdown automaton is normed iff from every reachable configuration there is a computation that completely empties the stack. The norm $\|\alpha\|$ of a BPA-process α is defined as the length of the shortest derivation sequence from α to ϵ, not counting τ-moves. A BPA Δ is **normed** if for every X in $Const(\Delta)$ we have $0 \leq \|X\| < \infty$. A BPA Δ is **totally normed** if for every X in $Const(\Delta)$ we have $0 < \|X\| < \infty$. We denote the classes of normed **BPA**, totally normed **BPA** and normed **PDA** processes by **nBPA**, **tnBPA** and **nPDA**, respectively.

We consider the semantic equivalences *weak bisimilarity* and *strong bisimilarity* [13] over labeled transition systems (e.g., those generated by BPA).

Definition 2.2 The action τ is a special 'silent' internal action. The *extended transition relation* '$\stackrel{a}{\Rightarrow}$' is defined by $E \stackrel{a}{\Rightarrow} F$ iff either $E = F$ and $a = \tau$, or $E \stackrel{\tau^i}{\to} E' \stackrel{a}{\to} E'' \stackrel{\tau^j}{\to} F$ for some $i, j \in \mathbb{N}_0$. A binary relation R over states in a labeled transition graph is a *weak bisimulation* iff whenever $(E, F) \in R$ then for every $a \in Act$: if $E \stackrel{a}{\to} E'$ then there is $F \stackrel{a}{\Rightarrow} F'$ s.t. $(E', F') \in R$ and if $F \stackrel{a}{\to} F'$ then there is $E \stackrel{a}{\Rightarrow} E'$ s.t. $(E', F') \in R$. States E, F are *weakly bisimilar*, written $E \approx F$, iff there is a weak bisimulation relating them. Strong bisimulation is defined similarly with $\stackrel{a}{\to}$ instead of $\stackrel{a}{\Rightarrow}$. E, F are *strongly bisimilar*, written $E \sim F$, iff there is a strong bisimulation relating them.

Bisimulation equivalence can also be described by *bisimulation games* [21] between two players. One player, the 'attacker', tries to prove that two given processes are not bisimilar, while the other player, the 'defender', tries to frustrate this. In every round of the game the attacker chooses one process and performs an action. The defender must imitate this move and perform the same action in the other process (possibly together with several internal

τ-actions in the case of weak bisimulation). If one player cannot move then the other player wins. The defender wins every infinite game. Two processes are bisimilar iff the defender has a winning strategy and non-bisimilar iff the attacker has a winning strategy.

We consider the problem of weak bisimulation equivalence of normed context-free processes (nBPA).

nBPA $\approx$ nBPA (Weak bisimilarity of normed BPA)

Instance: A set of BPA rules Δ and two normed processes α and α'.
Question: $(\alpha, \Delta) \approx (\alpha', \Delta)$?

We show an *EXPTIME*-lower bound for this problem by a polynomial-time reduction from the acceptance problem of alternating linear-bounded Turing machines.

Definition 2.3 An *alternating LBA* (alternating linear-bounded automaton) is a tuple $\mathcal{M} = (S, \Sigma, \gamma, s_0, \vdash, \dashv, \pi)$ where $S, \Sigma, \gamma, s_0, \vdash$, and $\dashv$ are defined as for ordinary non-deterministic LBA. In particular, S is a finite set of control states, $\vdash, \dashv \in \Sigma$ are the left-end and right-end markers, respectively, and $\pi : S \to \{\forall, \exists, acc, rej\}$ is a function which partitions the control states of S into *universal*, *existential*, *accepting*, and *rejecting*, respectively. We assume (w.l.o.g.) that γ is defined so that

- for all $s \in S$ and $A \in \Sigma$ such that $\pi(s) = \forall$ or $\pi(s) = \exists$ we have that $|\gamma(s, A)| = 2$ (i.e., $\gamma(s, A) = \{s_1, s_2\}$ for some $s_1, s_2 \in S$). The first element of $\gamma(s, A)$ is denoted by $first(s, A)$, and the second one by $second(s, A)$. It means that each configuration of $\mathcal{M}$ where the control state is universal or existential has exactly two immediate successors (configurations reachable in one computation step).
- for all $s \in S$ and $A \in \Sigma$ such that $\pi(s) = acc$ or $\pi(s) = rej$ we have that $\gamma(s, A) = \emptyset$, i.e., each configuration of $\mathcal{M}$ where the control state is accepting or rejecting is 'terminated' (without any successors).

A *computation tree* for $\mathcal{M}$ on a word $w \in \Sigma^*$ is a finite tree T satisfying the following: the root of T is (labeled by) the initial configuration $s_0 \vdash w \dashv$ of $\mathcal{M}$, and if N is a node of $\mathcal{M}$ labeled by a configuration usv where $u, v \in \Sigma^*$ and $s \in S$, then the following holds:

- if s is accepting or rejecting, then T is a leaf;

- if s is existential, then T has one successor whose label is one of the two configurations reachable from usv in one step (here, the notion of a computation step is defined in the same way as for 'ordinary' Turing machines);
- if s is universal, then T has two successors labeled by the two configurations reachable from usv in one step.

$\mathcal{M}$ *accepts* w iff there is a computation tree T such that all leaves of T are accepting configurations. The acceptance problem for alternating LBA is known to be *EXPTIME*-complete [6].

Remark 2.4 *We assume that all branches of the computation tree of an alternating LBA M on an input word w have a finite length, which is at most exponential in $|w|$. This is no restriction, since there are at most $|\Sigma|^{|w|}$ different tape configurations. For any alternating LBA M one could construct an equivalent one with the required property by counting the number of computation steps on the tape (using only linear space).*

3 The Idea

We prove *EXPTIME*-hardness of the **nBPA** $\approx$ **nBPA** problem by a reduction of the acceptance problem of alternating LBA to it. First, we describe the general ideas of our construction in an informal way.

For an alternating LBA $M = (S, \Sigma, \gamma, s_0, \vdash, \dashv, \pi)$ with input word w (of length n) we construct in polynomial time a normed BPA Δ and two processes α and α' s.t. M accepts w iff $\alpha \not\approx \alpha'$. We represent an LBA configuration as a sequence usv where $u \in \Sigma^*$ is the content of the tape to the left of the head, s is the control-state, and $v \in \Sigma^+$ is the content of the tape under the head and to the right of it. The construction ensures that the bisimulation game on α, α' proceeds in three phases.

Phase 1: First, a sequence of LBA configurations is pushed onto the stack in both processes. The attacker determines the tape symbols (from Σ) of these configurations and the successor control-states (from S) if the current control-state is existential. The defender determines the successor control-states (from S) if the current control-state is universal. (This is achieved by an application of the so-called 'existential quantification technique' which is due to Jančar [9]; a more explicit formulation

is due to Srba [17].) This construction does not guarantee that this sequence of configurations really is a correct computation of the LBA. However, the rest of the construction ensures that the attacker can win if and only if the sequence of configurations is a correct computation that ends in an accepting LBA configuration.

Phase 2: At an accepting LBA configuration the attacker can do the special action 'f' in process α and thus enter the next phase. Action 'f' is not immediately enabled in the process α'. Thus, the defender can only reply by popping the whole content of the stack of process α' (by τ-actions) and rebuilding the stack content (again by τ-actions). However, only incorrect computation sequences of the LBA can be generated in this way. This long defender-move ends with the visible action 'f'. This means that if the stack content of process α (on the attacker's side) is not a correct accepting computation sequence of the LBA then the defender can make the two processes syntactically equal (and thus weakly bisimilar). Otherwise the two resulting processes will not be syntactically equal (and also not weakly bisimilar as the next phase will show).

Phase 3: In the last phase the content of the stack will be popped by characteristic actions for each symbol. So, in this phase, the current processes will be weakly bisimilar if and only if they are syntactically equivalent.

Thus, the only way to win for the attacker is to push a sequence of LBA configurations onto the stack that represents a correct accepting computation sequence of the LBA. If the attacker can do this despite the defender's interference in choosing the successor control-states at the universal control-states, then the attacker will win. In any other case the game will either continue forever, or the defender can make the two processes syntactically equal and so the defender will win. Thus, the attacker can win iff M accepts w.

4 The Construction

For an alternating LBA $M = (S, \Sigma, \gamma, s_0, \vdash, \dashv, \pi)$ with input word w (of length n), we construct (in polynomial time) a normed BPA Δ with $\Gamma := \mathit{Const}(\Delta)$ and $\mathit{Act} := \mathit{Act}(\Delta)$ and processes $\alpha := (s_0, 0)s_0wB$ and $\alpha' := (s_0', 0)s_0wB$ such that $\mathcal{M}$ accepts w iff $\alpha \not\approx \alpha'$. We represent an LBA configuration as a sequence usv where $u \in \Sigma^*$ is the content of the tape to the

left of the head, s is the control-state, and $v \in \Sigma^+$ is the content of the tape under the head and to the right of it.

The set of constants Γ of the BPA is defined as $\Gamma := T \cup \Sigma \cup S \cup \{B, C, G, F\}$ where T (the top symbols) is a set of additional constants that occur only at the top of the stack in the processes α and α'. T is defined as follows: Let $S' := \{s' \mid s \in S\}$. $T := S \times \{0, \ldots, n-1\} \cup (S \times \Sigma) \times \{1, \ldots, n\} \cup S' \times \{0, \ldots, n-1\} \cup (S' \times \Sigma) \times \{1, \ldots, n\} \cup \{(\tilde{s}, 0) \mid s \in S\} \cup (S \times S) \times \{0\} \cup \{(E, j, i) \mid 1 \leq j \leq |ERROR|, 0 \leq i \leq n-3\}$. (The set $ERROR$ will be defined later.) For every state $s \in S$, the states s' and $\tilde{s}$ are seen as being associated to s. $Act := \Sigma \cup S \times \Sigma \cup S \cup \{a, b, c, f, \tau\}$. The set of transitions Δ is defined in several steps.

First we define the transition rules for phase 1:

1. $(s,i) \stackrel{X}{\to} (s, i+1)X$ for all $s \in S$, $X \in \Sigma$, $0 \leq i \leq n-2$;

2. $(s,i) \stackrel{(s,Y)}{\to} ((s,Y), i+1)sY$ for all $s \in S$, $Y \in \Sigma$, $0 \leq i \leq n-1$;

3. $((s,Y),i) \stackrel{X}{\to} ((s,Y), i+1)X$ for all $s \in S$, $X, Y \in \Sigma$, $0 \leq i \leq n-1$;

4. $(s',i) \stackrel{X}{\to} (s', i+1)X$ for all $s \in S$, $X \in \Sigma$, $0 \leq i \leq n-2$;

5. $(s',i) \stackrel{(s,Y)}{\to} ((s',Y), i+1)sY$ for all $s \in S$, $Y \in \Sigma$, $0 \leq i \leq n-1$;

6. $((s',Y),i) \stackrel{X}{\to} ((s',Y), i+1)X$ for all $s \in S$, $X, Y \in \Sigma$, $0 \leq i \leq n-1$;

7. $((s,Y),n) \stackrel{s_1}{\to} (s_1, 0)$ if $\pi(s) = \exists$ and $s_1 \in \gamma(s,Y)$;

8. $((s',Y),n) \stackrel{s_1}{\to} (s_1', 0)$ if $\pi(s) = \exists$ and $s_1 \in \gamma(s,Y)$;

9. $((s,Y),n) \stackrel{a}{\to} (\tilde{s}_1, 0)$ if $\pi(s) = \forall$ and $s_1 = \mathit{first}(s,Y)$;

10. $((s,Y),n) \stackrel{a}{\to} (\tilde{s}_2, 0)$ if $\pi(s) = \forall$ and $s_2 = \mathit{second}(s,Y)$;

11. $((s,Y),n) \stackrel{a}{\to} ((s_1,s_2), 0)$ if $\pi(s) = \forall$, $s_1 = \mathit{first}(s,Y)$, $s_2 = \mathit{second}(s,Y)$;

12. $((s',Y),n) \stackrel{a}{\to} (\tilde{s}_1, 0)$ if $\pi(s) = \forall$ and $s_1 = \mathit{first}(s,Y)$;

13. $((s',Y),n) \stackrel{a}{\to} (\tilde{s}_2, 0)$ if $\pi(s) = \forall$ and $s_2 = \mathit{second}(s,Y)$;

14. $((s_1,s_2),0) \stackrel{s_1}{\to} (s_1, 0)$

15. $((s_1,s_2),0) \stackrel{s_2}{\to} (s_2, 0)$

16. $(\tilde{s}_1, 0) \stackrel{s_1}{\to} (s_1', 0)$

17. $(\tilde{s}_1, 0) \xrightarrow{s_2} (s_2, 0)$

18. $(\tilde{s}_2, 0) \xrightarrow{s_1} (s_1, 0)$

19. $(\tilde{s}_2, 0) \xrightarrow{s_2} (s_2', 0)$

Now we define the transition rules for phase 2.

In this phase we need to make it possible to generate all incorrect computation sequences of the LBA. This is possible, since any incorrect computation sequence can be characterized as containing at least one error in a computation step, which can be detected locally, i.e., by comparing 3 symbols of an LBA configuration with the 3 symbols at the same tape location at the previous LBA configuration (see, e.g., [2, 3]). We now define the set *ERROR* that describes all these possible errors in computations. It consists of elements of the form $(err_1, err_2)_i$, (with $err_1, err_2 \in (\Sigma \cup S)^3$) that are pairs of strings of symbols that occur at the same position of successive LBA configurations. The set *ERROR* contains exactly those pairs that cannot occur in correct computations of the LBA M. Thus *ERROR* depends on M. To define this formally, we first construct the set *CORR* of all correct pairs of this form, i.e., the complement of *ERROR*.

$$CORR := \{(\alpha(i)\alpha(i+1)\alpha(i+2), \beta(i)\beta(i+1)\beta(i+2)) \mid \alpha \rightarrow_M \beta, 0 \leq i \leq n-2\}$$

where α, β are configurations of M (of length $n+1$, since the control-state is stored as well), $\alpha(i)/\beta(i)$ is the symbol at position i of α/β and $\alpha \rightarrow_M \beta$ means that β is a successor-configuration of α, according to the computation of M.

$$ERROR := \{(err_1, err_2)_1, \ldots, (err_1, err_2)_m\} := ((\Sigma \cup S)^3 \times (\Sigma \cup S)^3) - CORR$$

Thus, $|ERROR| = m \leq (|\Sigma| + |S|)^6$.

20. $((s, Y), n) \xrightarrow{\tau} \epsilon$ if $\pi(s) = rej$

21. $((s', Y), n) \xrightarrow{\tau} \epsilon$ if $\pi(s) = rej$

22. $((s, Y), n) \xrightarrow{f} C$ if $\pi(s) = acc$

23. $((s, Y), n) \xrightarrow{\tau} \epsilon$ if $\pi(s) = acc$

24. $((s', Y), n) \xrightarrow{\tau} \epsilon$ if $\pi(s) = acc$

25. $Z \xrightarrow{\tau} \epsilon$ for all $Z \in \Sigma \cup S$

26. $B \xrightarrow{\tau} GB$

27. $G \xrightarrow{\tau} GZ$ for all $Z \in \Sigma \cup S$

28. $G \xrightarrow{\tau} (E, j, 0)err_1$ for all $(err_1, err_2)_j \in ERROR$

29. $(E, j, i) \xrightarrow{\tau} (E, j, i+1)Z$ for all $Z \in \Sigma \cup S$, $0 \leq i \leq n-3$

30. $(E, j, n-2) \xrightarrow{\tau} Ferr_2$ for all $(err_1, err_2)_j \in ERROR$

31. $F \xrightarrow{\tau} FZ$ for all $Z \in \Sigma \cup S$

32. $F \xrightarrow{f} C$

Note that a series of τ-actions by rules 26–31 can push arbitrarily long sequences of symbols onto the stack. However, by definition of the set $ERROR$, none of these sequences represents a correct computation of the LBA M. Furthermore, this sequence of τ-actions must always end with the visible action 'f' (by rule 32). Finally, we define the transitions for phase 3.

33. $C \xrightarrow{c} \epsilon$

34. $Z \xrightarrow{Z} \epsilon$ for all $Z \in \Sigma \cup S$

35. $B \xrightarrow{b} \epsilon$

5 The Proof

We assume now that the alternating LBA M, the input word w, the BPA Δ and the processes α and α' are defined as in Section 4.

Lemma 5.1 *The following properties are equivalent.*

1. *M accepts w.*
2. *Starting with processes $\alpha := (s_0, 0)s_0wB$ and $\alpha' := (s_0', 0)s_0wB$, the attacker has a strategy in the weak bisimulation game to enforce (whatever the defender does) that the game reaches a configuration of processes $\beta = ((s, Y), n)\gamma B$ and $\beta' = ((s', Y), n)\gamma B$, where $\pi(s) = acc$ and γ is a sequence of LBA configurations that describes a correct accepting computation of M.*

Proof In the process α, by the rules 1–3, LBA configurations of length $n+1$ are pushed onto the stack (n tape symbols plus one symbol for the control-state). The control-state of the simulated LBA is stored in the top symbol of the stack. After the control-state has been pushed (by rule 2), it is stored in the top symbol of the stack together which the tape symbol under the head of the (simulated) LBA. Exactly the same is done in the process α' by rules 4–6. (The defender is forced to copy the attacker's moves. In this phase the only difference between α and α' is in the top symbol of the stack.) The attacker determines which tape symbols are pushed onto the stack.

After a configuration has been pushed onto the stack, the successor control-state is determined. If the current control-state is existential ($\pi(s) = \exists$) then the attacker determines the successor control-state by rule 7 (or 8). The defender must imitate this move by rule 8 (or 7 resp.). If the current control-state is universal ($\pi(s) = \forall$) then the attacker must apply rule 11 in process α. In any other case (if the attacker uses rule 9 or 10 in α or rule 12 or 13 in α') the defender can make the two processes syntactically equal (by rule 9,10,12 or 13) in the same round and wins. The defender then chooses the successor control-state by applying either rule 12 or rule 13 in α'. We now assume that the defender chose rule 12, i.e., control-state s_1. The other case is symmetric. Then the top symbols of α and α' are $((s_1, s_2), 0)$ and $(\tilde{s}_1, 0)$, respectively. The attacker must now play a rule with action s_1 (either 14 in α or 16 in α') which yields the new top symbols $(s_1, 0)$ and $(s_1', 0)$ of α and α', respectively. If the attacker chooses rule 15 or 17 then the two processes become syntactically equal and the defender wins. The effect of this construction is, that at universal control-states s it is the defender who chooses between the two possible successor control-states s_1 and s_2.

$\Rightarrow$ If M accepts w then, by Definition 2.3, there is a computation tree of M on w where all branches end with an accepting leaf. By the construction above the attacker selects the tree and the defender selects the branch. By pushing only correct successor configurations of the LBA onto the stack, the attacker creates a stack content γ that corresponds to a branch in the accepting tree. The defender can only copy his moves in the other process. Thus a configuration of processes $\beta = ((s, Y), n)\gamma B$ and $\beta' = ((s', Y), n)\gamma B$ is reached, where $\pi(s) = acc$ and γ is a sequence of LBA configurations that describes a correct accepting computation of M.

$\Leftarrow$ If M does not accept w then, by Definition 2.3, every computation tree has at least one branch that does not accept. By the construction above the defender can select the successor control-states at the universal

nodes in such a way that a non-accepting branch of the computation-tree is chosen. Therefore, if the attacker chooses to push the right tape symbols onto the stack (s.t. a correct computation sequence of M is pushed onto the stack) this will end in a rejecting configuration. However, the attacker might also introduce errors into the computation by pushing wrong LBA configurations onto the stack and thus reach a pair of configurations $\beta = ((s, Y), n)\gamma B$ and $\beta' = ((s', Y), n)\gamma B$, where $\pi(s) = acc$ and γ is **not** a correct computation sequence of the LBA. In either case it is impossible for the attacker to enforce a configuration of processes $\beta = ((s, Y), n)\gamma B$ and $\beta' = ((s', Y), n)\gamma B$, where $\pi(s) = acc$ and γ is a sequence of LBA configurations that describes a correct accepting computation of M. ■

Lemma 5.2 *Let $\gamma, \gamma' \in (\Sigma \cup S)^*$. We have $\gamma B \approx \gamma' B$ if and only if $\gamma = \gamma'$*

Proof The 'if' direction is trivial. For the 'only if' direction assume that $\gamma \neq \gamma'$ and (without restriction) $|\gamma| \geq |\gamma'|$. We prove $\gamma B \not\approx \gamma' B$ by induction on $|\gamma'|$.

In the base case $|\gamma'| = 0$ and $|\gamma| > 0$, since $\gamma \neq \gamma'$. Thus $\gamma B \stackrel{Z}{\rightarrow} \delta B$ (by rule 34) for some $Z \in \Sigma \cup S$, but $\gamma' B = B \stackrel{Z}{\not\Rightarrow}$. So the attacker wins and $\gamma B \not\approx \gamma' B$.

For the induction step the attacker plays $\gamma B \stackrel{Z}{\rightarrow} \delta B$ by rule 34 (i.e., he removes the top symbol Z of γ). The defender can respond in two ways. First, if the top symbol of γ' is the same Z as that of γ then the defender can play $\gamma' B \stackrel{Z}{\rightarrow} \delta' B$ by rule 34. It follows that $\delta \neq \delta'$ and $|\delta'| = |\gamma'| - 1$. By induction hypothesis $\delta B \not\approx \delta' B$. Second, if the symbol Z occurs at some other position in γ' then the defender can play $\gamma' B \stackrel{Z}{\Rightarrow} \delta' B$ (by rules 25. and 34.). However, in this case $|\delta'| < |\gamma'| - 1$ while $|\delta| = |\gamma| - 1$. Therefore $|\delta'| < |\delta|$ and thus $\delta' \neq \delta$. By induction hypothesis again $\delta B \not\approx \delta' B$. (Using the rules 26–32 to generate new symbols on the stack is not an option for the defender, since this always ends with the visible action 'f'.) Thus, the attacker has a winning strategy and $\gamma B \not\approx \gamma' B$. ■

Lemma 5.3 *$B \stackrel{\tau^*}{\rightarrow} \stackrel{f}{\rightarrow} C\gamma B$ if and only if $\gamma \in (\Sigma \cup S)^*$ is not a correct computation of M.*

Proof Directly from the definition of the set *ERROR* and the rules 26–32. ■

Lemma 5.4 *Let $\beta = ((s,Y),n)\gamma B$ and $\beta' = ((s',Y),n)\gamma B$ be processes, where $\pi(s) = acc$. We have $\beta \not\approx \beta'$ if and only if γ is a correct computation sequence of the LBA M.*

Proof

$\Rightarrow$ We assume that γ is not a correct computation sequence of M and show that $\beta \approx \beta'$ under this condition. The defender has the following winning strategy. If the attacker plays $\beta = ((s,Y),n)\gamma B \stackrel{\tau}{\rightarrow} \gamma B$ or $\beta' = ((s',Y),n)\gamma B \stackrel{\tau}{\rightarrow} \gamma B$ then the defender can make the two processes syntactically equal in the same round of the game and wins. If the attacker plays $\beta = ((s,Y),n)\gamma B \stackrel{f}{\rightarrow} C\gamma B$ then the defender can reply by $\beta' = ((s',Y),n)\gamma B \stackrel{\tau^*}{\rightarrow} B \stackrel{\tau^*}{\rightarrow}\stackrel{f}{\rightarrow} C\gamma B$ by Lemma 5.3, because γ is not a correct computation sequence of M. Again the two processes are syntactically equal and the defender wins. Thus $\beta \approx \beta'$.

$\Leftarrow$ If γ is a correct computation sequence of the LBA M then the attacker has the following winning strategy. The attacker plays $\beta = ((s,Y),n)\gamma B \stackrel{f}{\rightarrow} C\gamma B$. The defender can only reply by popping the whole stack (by rules 24 and 25), pushing a new sequence of symbols onto the stack (by rules 26–31) and finally doing action 'f' (by rule 32). So the defender can only play $\beta' = ((s',Y),n)\gamma B \stackrel{\tau^*}{\rightarrow} B \stackrel{f}{\Rightarrow} C\gamma' B$. However, by Lemma 5.3, γ' does not represent a correct computation of M and thus $\gamma' \neq \gamma$. Now there are two cases.

If $|\gamma| \geq |\gamma'|$ then the attacker plays $C\gamma B \stackrel{c}{\rightarrow} \gamma B$ to which the defender can only reply $C\gamma' B \stackrel{c}{\Rightarrow} \gamma'' B$, where γ'' is a suffix of γ' (by rules 33 and 25). Thus $\gamma \neq \gamma''$ and, by Lemma 5.2, $\gamma B \not\approx \gamma'' B$ and so the attacker wins.

If $|\gamma| < |\gamma'|$ then the attacker changes sides and plays $C\gamma' B \stackrel{c}{\rightarrow} \gamma' B$. The defender can only reply by $C\gamma B \stackrel{c}{\Rightarrow} \gamma''' B$, where γ''' is a suffix of γ. We get $|\gamma'''| < |\gamma'|$ and thus $\gamma''' \neq \gamma'$. By Lemma 5.2 $\gamma''' B \not\approx \gamma' B$ and so the attacker wins.

Therefore the attacker has a winning strategy and $\beta \not\approx \beta'$. ■

Lemma 5.5 *Let $\alpha := (s_0,0)s_0 wB$ and $\alpha' := (s_0',0)s_0 wB$. $\alpha \not\approx \alpha'$ if and only if M accepts w.*

Proof

$\Leftarrow$ If M accepts w then the attacker has the following winning strategy. By Lemma 5.1 the attacker has a strategy in the weak bisimulation game to reach a configuration of processes $\beta = ((s, Y), n)\gamma B$ and $\beta' = ((s', Y), n)\gamma B$, where $\pi(s) = acc$ and γ is a sequence of LBA configurations that describes a correct computation of M. (It must be a correct accepting computation on w, since it starts with w and $\pi(s) = acc$). By Lemma 5.4 $\beta \not\approx \beta'$ and the attacker wins. Thus $\alpha \not\approx \alpha'$.

$\Rightarrow$ If M does not accept w then the defender has a winning strategy. By Lemma 5.1 the defender has a strategy to **avoid** a configuration $\beta = ((s, Y), n)\gamma B$ and $\beta' = ((s', Y), n)\gamma B$, where $\pi(s) = acc$ and γ is a sequence of LBA configurations that describes a correct computation of M. The defender plays according to this strategy until one of the following two situations occurs: If the top symbols correspond to a rejecting state then only rules 20 and 21 are applicable, the processes become syntactically equal and the defender wins. If the top symbols correspond to accepting states then the two current processes must have the form $\beta = ((s, Y), n)\gamma B$ and $\beta' = ((s', Y), n)\gamma B$, where $\pi(s) = acc$. By Lemma 5.1 γ does not represent a correct accepting computation of M and thus by Lemma 5.4 $\beta \approx \beta'$. So the defender always wins and $\alpha \approx \alpha'$. ■

Lemma 5.6 *Let Δ be the BPA from Section 4, depending on the alternating LBA M. It is normed for every M.*

Proof All constants $Z \in \Sigma \cup S$ have norm 0, because of rule 25. Constants B and C have norm 1, because of rules 35 and 33. $\|F\| = \|C\| + 1 = 2$, by rule 32. $\|G\| = 2$, because of rules 28–30, 32, 33 and 25. All constants $t \in T$ have finite norm, because by Remark 2.4 all correct computation sequences of M have finite length. It is possible to push a correct computation sequence of M onto the stack. This sequence will end in an accepting or a rejecting state after an at most exponential number of steps by Remark 2.4. Thus all constants in T have finite norm, because of rules 1–24, 33 and 25. Therefore all constants in Γ have finite norm. ■

Note that our system Δ is normed, but not totally normed (see Def. 2.1), because some constants have norm 0.

Theorem 5.7 *Weak bisimulation equivalence for normed BPA is EXPTIME-hard.*

Proof By reduction of the acceptance problem for alternating linear-bounded Turing machines. For any alternating LBA M with input word w we construct the BPA Δ and processes α, α' as in Section 4. By Lemma 5.6 the BPA is normed and by Lemma 5.5 $\alpha \not\approx \alpha'$ if and only if M accepts w. ■

6 The Regularity Problem

The regularity problem is to check if a given infinite-state process is regular (i.e., finite) up-to a given notion of semantic equivalence.

Weak regularity of BPA

Instance: A BPA process (P, Δ).
Question: Is there a finite-state system F s.t. $(P, \Delta) \approx F$?

We show that weak regularity of BPA is *EXPTIME*-hard by a modification of the construction of Section 4. The problem with the construction from Section 4 is, that it is possible to generate infinitely many different wrong computation sequences (of the LBA) on the stack, which are all pairwise non-weakly-bisimilar. Thus our processes α, α' are always infinite (i.e., non-regular) up-to weak bisimilarity. Here we modify our construction to make the processes regular up-to weak bisimilarity. (The idea is to make all the processes containing wrong computation sequences (of the LBA) weakly bisimilar to each other.) Then we use a standard reduction (from [15]) from weak bisimilarity of weakly regular processes to the weak regularity problem. However, unlike in Section 4, our modified processes are not normed.

The modification of the construction is done as follows:

- We replace the old rule 25: $Z \stackrel{\tau}{\rightarrow} \epsilon$ (for all $Z \in \Sigma \cup S$) by the new rule 25: $Z \stackrel{\tau}{\rightarrow} GB$ (for all $Z \in \Sigma \cup S$).
- We replace the old rule 35: $B \stackrel{b}{\rightarrow} \epsilon$ by the new rule 35: $B \stackrel{b}{\rightarrow} B$. (Thus the new system is no longer normed, since $\|B\| = \infty$.)
- We add the new rule number 36: $F \stackrel{\tau}{\rightarrow} \epsilon$.

Let Δ' be this new modified set of rules. We obtain that $\gamma B \approx \gamma' B$ for all computation sequences γ, γ' (of the alternating LBA) that contain at least one error, because all sequences with errors can be generated by τ-actions. Formally, we show a modified version of Lemma 5.2 for the new system Δ' as follows:

Lemma 6.1 *Let $\gamma, \gamma' \in (\Sigma \cup S)^*$. If γ and γ' are incorrect computation sequences (of the alternating LBA) then $\gamma B \approx \gamma' B$. If γ is a correct computation sequence and $\gamma' \neq \gamma$ then $\gamma B \not\approx \gamma' B$.*

Proof

1. Let $\gamma, \gamma' \in (\Sigma \cup S)^*$ be incorrect computation sequences (of the alternating LBA). Then the defender has the following winning strategy in the weak bisimulation game starting at $\gamma B, \gamma' B$. Let $Z, Z' \in \Sigma \cup S$ be the first symbols in γ, γ' respectively, i.e., $\gamma = Z\delta$ and $\gamma' = Z'\delta'$. (Z, Z' exist, since the empty sequence is a correct computation sequence, because it does not contain any wrong steps.) There are only two possibilities for the attacker move:

   (a) If the attacker plays $\gamma B = Z\delta B \xrightarrow{\tau} GB\delta B$ by the new rule 25 then the defender responds by $\gamma' B = Z'\delta' B \xrightarrow{\tau} GB\delta' B$ (by rule 25), and vice versa. Since $\|B\| = \infty$ we have $GB\delta B \approx GB \approx GB\delta' B$ and thus the defender can win.

   (b) If the attacker plays $\gamma B = Z\delta B \xrightarrow{Z} \delta B$ (by rule 34) then the defender responds by a long move: First $\gamma' B = Z'\delta' B \xrightarrow{\tau} GB\delta' B$ by rule 25. Then $GB\delta' B \xrightarrow{\tau^*} F\gamma B\delta' B$ by rules 27–31 (this is possible, because γ is an incorrect computation sequence of the alternating LBA). Then $F\gamma B\delta' B \xrightarrow{\tau} \gamma B\delta' B = Z\delta B\delta' B$ (by the new rule 36). Finally, $Z\delta B\delta' B \xrightarrow{Z} \delta B\delta' B$ by rule 34. Since $\|B\| = \infty$ we have $\delta B \approx \delta B\delta' B$ and thus the defender can win.

   The other case where the attacker plays $\gamma' B = Z'\delta' B \xrightarrow{Z'} \delta' B$ is symmetric, because γ' is also an incorrect computation sequence of the alternating LBA.

   Thus the defender has a winning strategy and so $\gamma B \approx \gamma' B$.

2. Now we assume that γ is a correct computation sequence and $\gamma' \neq \gamma$. We show that $\gamma B \not\approx \gamma' B$ by induction on $|\gamma|$. We describe a winning strategy for the attacker in the weak bisimulation game.

   In the base case $|\gamma| = 0$ and $|\gamma'| > 0$, since $\gamma \neq \gamma'$. Thus $\gamma B = B \xrightarrow{b} B$ (by rule 35), but $\gamma' B \not\xRightarrow{b}$. So the attacker wins and $\gamma B \not\approx \gamma' B$.

   For the induction step $|\gamma| \geq 1$ and thus $\gamma = Z\delta$ for some $Z \in (\Sigma \cup S)$ and $\delta \in (\Sigma \cup S)^*$. In the special case that $|\gamma'| = 0$ we have $\gamma' B = B \xrightarrow{b} B$ (by rule 35), but $\gamma B = Z\delta B \not\xRightarrow{b}$. So the attacker wins and $\gamma B \not\approx \gamma' B$. So we now assume $|\gamma'| \geq 1$ and thus $\gamma' = Z'\delta'$ for some $Z' \in (\Sigma \cup S)$

and $\delta' \in (\Sigma \cup S)^*$. The attacker plays $\gamma B = Z\delta B \xrightarrow{Z} \delta B$ (by rule 34). The defender can respond in two ways:

(a) If $Z = Z'$ then the defender can do $\gamma' B = Z'\delta' B = Z\delta' B \xrightarrow{Z} \delta' B$ (by rule 34). Then δ is still a correct computation sequence of the LBA and $\delta' \neq \delta$. Furthermore, $|\delta| < |\gamma|$. Thus, by induction hypothesis $\delta B \not\approx \delta' B$ and so the attacker can win.

(b) In any case (if $Z = Z'$ or not) the defender can do $\gamma' B = Z'\delta' B \stackrel{Z}{\Rightarrow} \delta'' B \delta' B$ by rules 27–31, 36 and 34, where δ'' is an incorrect computation sequence of the LBA and $|\delta''| > 0$. We get $\delta'' B \delta' B \approx \delta'' B$. Again we have that δ is a correct computation sequence, $\delta' \neq \delta$ and $|\delta| < |\gamma|$. By induction hypothesis $\delta B \not\approx \delta'' B$ and so the attacker can win.

Thus the attacker has a winning strategy and so $\gamma B \not\approx \gamma' B$. ■

Theorem 6.2 *Weak regularity of BPA is EXPTIME-hard.*

Proof We use the modified set of rules Δ' as described above. By Lemma 6.1 all the infinitely many incorrect computation sequences are weakly bisimilar to each other. Since, by Remark 2.4, all correct computation sequences have exponentially bounded length, it follows that the processes α, α' (defined as in Section 4) in the new system Δ' are finite up to weak bisimilarity, i.e., weakly regular. However, they still satisfy the property $\alpha \not\approx \alpha'$ iff M accepts w, because

- Lemma 5.1 carries over directly to Δ'.
- Lemma 5.2 is replaced by Lemma 6.1 for Δ'.
- Lemma 5.3 carries over directly to Δ'.
- Lemma 5.4 carries over to Δ'. The proof must be modified slightly to use Lemma 6.1 instead of Lemma 5.2. Also the long moves of popping the whole stack (by rule 25 in Δ) till the bottom symbol B and generating a new stack content (by rules 26–31) are modified. By the new rule 25 in Δ' the stack content is not popped but cut off by the introduction of a new bottom symbol B, which cannot be removed in Δ'. (Remember that in Δ' we have $\|B\| = \infty$ and thus $\gamma B \delta \approx \gamma B$ for all γ, δ.)
- Lemma 5.5 carries over directly to Δ'.

Note that Lemma 5.6 does **not** carry over to Δ', since $\|B\| = \infty$.

So we obtain that (α, Δ'), (α', Δ') are weakly regular and $(\alpha, \Delta') \not\approx (\alpha', \Delta')$ if and only if M accepts w.

Then we can apply the general polynomial time reduction from weak bisimilarity of weakly regular BPA (which we have just shown to be *EXPTIME*-hard) to the weak regularity problem for BPA from [15] and obtain our result. ■

7 Conclusion

We have shown an *EXPTIME* lower bound for the problem of checking weak bisimulation equivalence for general and normed BPA. However, our result does not carry over to the class of totally normed BPA. The following table summarizes the known complexity results about strong and weak bisimilarity on PDA and BPA. New results are in boldface. (For an extensive list of results on the complexity of bisimulation checking for infinite-state systems see [16].)

	(n)PDA	**BPA**	**nBPA**	**tnBPA**
$\sim$	decidable [14] *EXPTIME*-hard [10]	in 2-*EXPTIME*[5] *PSPACE*-hard [18]	P-complete [8, 1]	P-complete [8, 1]
$\approx$	undecidable [19]	? **EXPTIME-hard**	? **EXPTIME-hard**	decidable [7] $\mathcal{NP}$-hard [22]

It is interesting to compare these results with the results on checking bisimilarity with finite-state systems. For example, checking strong and weak bisimilarity between (normed) PDA and finite-state systems is *PSPACE*-complete [10] and checking weak (and strong) bisimilarity between BPA and finite-state systems is polynomial [11].

Furthermore, we have shown a new *EXPTIME* lower bound for weak regularity of BPA. For normed BPA, the best known lower bound for weak regularity is still $\mathcal{NP}$-hardness [15]. For totally normed BPA, weak regularity coincides with boundedness, which is **NLogspace**-complete [18].

References

[1] J. Balcazar, J. Gabarro, and M. Santha. Deciding bisimilarity is P-complete. *Formal Aspects of Computing*, 4:638–648, 1992.

[2] A. Bouajjani, J. Esparza, and O. Maler. Reachability analysis of pushdown automata: application to model checking. In *International Conference on Concurrency Theory (CONCUR'97)*, volume 1243 of *LNCS*. Springer Verlag, 1997.

[3] A. Bouajjani, J. Esparza, and O. Maler. Reachability Analysis of Pushdown Automata: Application to Model Checking. Technical report, VERIMAG, 1997. ftp://ftp.imag.fr/imag/SPECTRE/ODED/pda.ps.gz.

[4] O. Burkart, D. Caucal, F. Moller, and B. Steffen. Verification on infinite structures. In J. Bergstra, A. Ponse, and S. Smolka, editors, *Handbook of Process Algebra*, chapter 9, pages 545–623. Elsevier Science, 2001.

[5] O. Burkart, D. Caucal, and B. Steffen. An elementary bisimulation decision procedure for arbitrary context-free processes. In *MFCS'95*, volume 969 of *LNCS*. Springer Verlag, 1995.

[6] A. K. Chandra, D. C. Kozen, and L. J. Stockmeyer. Alternation. *Journal of the ACM*, 28(1):114–133, 1981.

[7] Y. Hirshfeld. Bisimulation trees and the decidability of weak bisimulations. *Electronic Notes in Theoretical Computer Science (ENTCS)*, 5, 1997.

[8] Y. Hirshfeld, M. Jerrum, and F. Moller. A polynomial algorithm for deciding bisimilarity of normed context-free processes. *Theoretical Computer Science*, 158:143–159, 1996.

[9] P. Jančar. High undecidability of weak bisimilarity for Petri nets. In *Proceedings of CAAP'95*, volume 915 of *LNCS*, pages 349–363. Springer, 1995.

[10] A. Kučera and R. Mayr. On the complexity of semantic equivalences for pushdown automata and BPA. In *Proc. of MFCS 2002*, volume 2420, pages 433–445. Springer Verlag, 2002.

[11] A. Kučera and R. Mayr. Weak bisimilarity between finite-state systems and BPA or normed BPP is decidable in polynomial time. *Theoretical Computer Science*, 270:667–700, 2002.

[12] R. Mayr. Process rewrite systems. *Information and Computation*, 156(1):264–286, 2000.

[13] R. Milner. *Communication and Concurrency*. Prentice Hall, 1989.

[14] G. Sénizergues. Decidability of bisimulation equivalence for equational graphs of finite out-degree. In *Proc. of FOCS'98*. IEEE, 1998.

[15] J. Srba. Complexity of weak bisimilarity and regularity for BPA and BPP. *Electronic Notes in Theoretical Computer Science (ENTCS)*, 39, 2000. Proceedings of the 7th International Workshop on Expressiveness in Concurrency (EXPRESS'00).

[16] J. Srba. Roadmap of infinite results. *Bulletin of the European Association for Theoretical Computer Science*, 78:163–175, October 2002. Columns: Concurrency. Regularly updated online version at `http://www.brics.dk/~srba/roadmap`.

[17] J. Srba. Strong bisimilarity and regularity of basic parallel processes is PSPACE-hard. In *Proceedings of STACS 2002*, volume 2285 of *LNCS*, pages 535–546. Springer, 2002.

[18] J. Srba. Strong bisimilarity and regularity of basic process algebra is PSPACE-hard. In *Proc. of ICALP 2002*, volume 2380 of *LNCS*, pages 716–727. Springer Verlag, 2002.

[19] J. Srba. Undecidability of weak bisimilarity for pushdown processes. In *Proc. of CONCUR 2002*, volume 2421 of *LNCS*, pages 579–593. Springer Verlag, 2002.

[20] C. Stirling. Decidability of bisimulation equivalence for normed pushdown processes. *Theoretical Computer Science*, 195:113–131, 1998.

[21] C. Stirling. The joys of bisimulation. In *Proc. of MFCS'98*, volume 1450 of *LNCS*, pages 142–151. Springer Verlag, 1998.

[22] J. Stříbrná. Hardness results for weak bisimilarity of simple process algebras. *Electronic Notes in Theoretical Computer Science (ENTCS)*, 18, 1998.